

MULTICORE CONNECTORS FOR AUXILIARIES

The HVSL Multicore Series is characterized by high performance and maximum safety. It meets the requirements of LV215 for electric vehicle applications.

The applied multicore cable simplifies the collective transportation of signals and facilitates handling.

Integrated HVIL contacts and various coding options give you maximum flexibility. These plugs are specially designed for DC-DC, AC and other equipment in xEV device applications.



Criteria	HVSL 282	HVSL 635
Temperature Range	-40 to 125 °C	-40 to 125 °C
IP-Rating	IP67, IP6X9K	IP67, IP6K9K
Touchproof	IP2XB	IP2XB
Rated Current	up to 32 A	40 A
Voltage Rating	1000 V DC	850 V DC
Mating cycles	50 cycles	50 cycles
Cable OD 2.4mm ²	9.9+0/-0.6	
Cable OD 4mm ²	11.3+0/-0.6	
Cable OD 6mm ²		16.3+0/-0.6 14.7+/-0.3

KEY FEATURES:

- Multicore cables facilitate handling
- Integrated internal HVIL
- Two-stage, tool or thumb activated
- No tool required to unmate
- Multiple coding positions
- RoHS & REACH certificated
- CPA



Contact us for product related information:
+49 7131 929 0
industrial@amphenol.de



**ENABLING THE
E-MOBILITY REVOLUTION**

Discover more at
www.amphenol-industrial.de

